



TactTiles LAYING INSTRUCTIONS

1. Plan your layout before you start ensuring cut edges are in the least conspicuous areas.
2. Ensure that all the tiles are facing the same way - check the lugs.
3. Start at one side of the floor, on a straight edge, or from the entrance to the room / building.
4. Place the plain side of the tile over the lugs and tap in place with a rubber mallet.
5. Tiles can be trimmed using a hacksaw or an electric jig saw. Mark where you want to cut using either a thick pencil or chalk. Cut to fit and tap into place.
6. Should you need to fasten down an edge, then place screws through the thickest point of the tile i.e. where the floor supports intersect. Countersink the screw heads so that they are flat with the top of the tile. In damp situations use stainless steel screws.
7. Any protruding 'lugs' can be removed if required with a sharp tap of a chisel for a neat edge.
8. **For Metro, Briq, Piazza, Elite & Nova Tiles:** Edgetiles can be connected to any side of these tiles.
9. **Expansiontile instructions for Pedestrian, Premium & Fitness & MultiSport Tiles:** install as per instructions above, but place a row of Expansiontiles every ten tiles in each direction, or as shown on your design plan.
10. Where two rows of Expansiontiles intersect, insert a Crosspiece.
11. You will find a pack of Linking-lugs enclosed which can be used to join two straight edges or reverse fit the Edgetiles onto a straight edge. (300mm² network pattern tiles only).
12. When laying Edges, allow a gap for movement when 'crossing over' the Expansion pieces.